

Need Assistance? Call 480-641-9733 7:30 to 2:30 PST. Let us help!
Be sure to set "Page Scaling" to "None" in printer setup.

INSERT THIS SIDE UP, THIS END FIRST
USE BLACK INK, FILL OVALS COMPLETELY

section 1

☐ Pulse/Serial ☐ \$1/\$5 Credit Lines
☐ MDB ☐ \$1-\$20 Credit Lines
☐ RS-232 Always Enabled
☐ Parallel Hi
☐ Special 1 Special 2

Select only one Interface Type

section 2

Example: For 50 pps, fill in the ovals for 32, 16, and 2 (32+16+2 = 50)

Pulses per Dollar (sum of selected values)

☐ 64 ☐ 4
☐ 32 ☐ 2
☐ 16 ☐ 1
☐ 8 ☐ None

section 3

Pulse Speed: ☐ Slow ☐ Fast
Lighted Bezel: ☐ Solid On ☐ Flashing

section 4

Select Bills to Enable

☐ Bill 1 (\$1) ☐ Bill 2 (\$5)
☐ Bill 3 (\$10) ☐ Bill 4 (\$20)
☐ Bill 5 (\$50) ☐ Bill 6 (\$100)
☐ Bill 7 ☐ Bill 8
Example: To accept USA \$1, \$5, and \$10, fill in the ovals for Bill 1, Bill 2, and Bill 3.

section 5

Security Level: ☐ High ☐ Low
Insert Direction: ☐ Face up, Left 1st ☐ All 4 Ways

This Configuration Card should be printed on standard copy paper, measuring 6.0 x 2.6 inches (152 x 66 mm).
If printing from a .PDF file, turn off the "shrink to fit" option in your printer settings for proper scale.

PYRAMID TECHNOLOGIES, INC.
CURRENCY VALIDATION EXPERTS

INSERT THIS SIDE UP, THIS END FIRST
USE BLACK INK, FILL OVALS COMPLETELY

section 1

☐ Pulse/Serial ☐ \$1/\$5 Credit Lines
☐ MDB ☐ \$1-\$20 Credit Lines
☐ RS-232 Always Enabled
☐ Parallel Hi
☐ Special 1 Special 2

Select only one Interface Type

section 2

Example: For 50 pps, fill in the ovals for 32, 16, and 2 (32+16+2 = 50)

Pulses per Dollar (sum of selected values)

☐ 64 ☐ 4
☐ 32 ☐ 2
☐ 16 ☐ 1
☐ 8 ☐ None

section 3

Pulse Speed: ☐ Slow ☐ Fast
Lighted Bezel: ☐ Solid On ☐ Flashing

section 4

Select Bills to Enable

☐ Bill 1 (\$1) ☐ Bill 2 (\$5)
☐ Bill 3 (\$10) ☐ Bill 4 (\$20)
☐ Bill 5 (\$50) ☐ Bill 6 (\$100)
☐ Bill 7 ☐ Bill 8
Example: To accept USA \$1, \$5, and \$10, fill in the ovals for Bill 1, Bill 2, and Bill 3.

section 5

Security Level: ☐ High ☐ Low
Insert Direction: ☐ Face up, Left 1st ☐ All 4 Ways

This Configuration Card should be printed on standard copy paper, measuring 6.0 x 2.6 inches (152 x 66 mm).
If printing from a .PDF file, turn off the "shrink to fit" option in your printer settings for proper scale.

PYRAMID TECHNOLOGIES, INC.
CURRENCY VALIDATION EXPERTS

INSERT THIS SIDE UP, THIS END FIRST
USE BLACK INK, FILL OVALS COMPLETELY

section 1

☐ Pulse/Serial ☐ \$1/\$5 Credit Lines
☐ MDB ☐ \$1-\$20 Credit Lines
☐ RS-232 Always Enabled
☐ Parallel Hi
☐ Special 1 Special 2

Select only one Interface Type

section 2

Example: For 50 pps, fill in the ovals for 32, 16, and 2 (32+16+2 = 50)

Pulses per Dollar (sum of selected values)

☐ 64 ☐ 4
☐ 32 ☐ 2
☐ 16 ☐ 1
☐ 8 ☐ None

section 3

Pulse Speed: ☐ Slow ☐ Fast
Lighted Bezel: ☐ Solid On ☐ Flashing

section 4

Select Bills to Enable

☐ Bill 1 (\$1) ☐ Bill 2 (\$5)
☐ Bill 3 (\$10) ☐ Bill 4 (\$20)
☐ Bill 5 (\$50) ☐ Bill 6 (\$100)
☐ Bill 7 ☐ Bill 8
Example: To accept USA \$1, \$5, and \$10, fill in the ovals for Bill 1, Bill 2, and Bill 3.

section 5

Security Level: ☐ High ☐ Low
Insert Direction: ☐ Face up, Left 1st ☐ All 4 Ways

This Configuration Card should be printed on standard copy paper, measuring 6.0 x 2.6 inches (152 x 66 mm).
If printing from a .PDF file, turn off the "shrink to fit" option in your printer settings for proper scale.

PYRAMID TECHNOLOGIES, INC.
CURRENCY VALIDATION EXPERTS